

• The MS technical features

Frames	Rigid						Folding									
	Monobar						Monobar 125		Double bar			Compact		Double bar		
Width	2m	2.2m	2.6m	3m	3.5m	3.8m	3m	4.5m	5.7m	6.6m	8.4m	6m	6.3m	6m	7m	
Transporting width (with long transport rack)	2m	2.2m	2.6m	3m	3.5m	3.8m	3m	4.5m	5.7m (2.5m)	6.6m (2.5m)	8.4m (2.5m)	3.5m	4.1m	3.5m	3.7m	
Number of rows maximum ⁽¹⁾	Element MS A	6	7	8	9	9	12	9	12	18	18	24	18	18	18	24
	Element MS B or B2	8	10	12	12	16	16	16	■	24	30	■	■	■	24	■
	Element MS C	6	7	8	9	9	12	9	12	18	18	24	18	18	18	24
	Element MS D or D2	4	5	6	6	8	8	6	■	12	12	■	-	-	12	■
Turbine	Power take-off drive - standard 540 rpm, optional 450 or 1.000 rpm. Hydraulic drive optional. Universal joint freewheel optional						Power take-off drive - standard 540 rpm, optional 450 or 1.000 rpm. Hydraulic drive optional. Universal joint freewheel optional									
Tyres	2 x (500 x 15)						2 x (500 x 15)		4 x (500 x 15)			4 x (500 x 15)		4 x (500 x 15)		
Distance gearbox (16 speeds)	1	1	1	1	1	1 (on 2)	1	1	1	1 (on 2)	2	3	3	3	3	3
Hydraulic markers	○	○	○	○	○	○	○	○	○	○	○	●	●	●	●	
Fertilizer	-	-	-	-	-	-	○	○	-	-	-	-	-	-	-	
Micromer	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Hectare counter	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Sowing controller	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Lighting kit	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Chassis weight (without elements)	290kg	290kg	320kg	320kg	360kg	410kg	550kg	580kg	700kg	750kg	1300kg	1150kg	1300kg	1220kg	1200kg	

- Standard
- Optional
- Inquire
- * According to model
- (1) According to power
- Contact us

For other models, configurations or other types: